



## MULTI/JOINT® 3407 Plus Wide Range Bend, restraint, Uni/Fiksers

### Model:



- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- Hygiene protection included DN50 - DN825

### Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information

### Note:

ID min. = minimum insertion depth



| DN<br>(mm) | Range 1<br>(mm) | Range 3<br>(mm) | NBR / A2<br>Code | EPDM / A2<br>Code | Weight<br>(kg) |
|------------|-----------------|-----------------|------------------|-------------------|----------------|
| 80         | 84 - 105        | 84 - 105        | 709 475 214      | 709 475 614       | 9.200          |
| 100        | 104 - 132       | 104 - 132       | 709 475 216      | 709 475 616       | 13.400         |
| 150        | 154 - 192       | 154 - 192       | 709 475 220      | 709 475 620       | 26.300         |

| DN<br>(mm) | NBR / A4<br>Code | EPDM / A4<br>Code | Weight<br>(kg) |
|------------|------------------|-------------------|----------------|
| 80         | 709 475 014      | 709 475 314       | 9.200          |
| 100        | 709 475 016      | 709 475 316       | 13.400         |
| 150        | 709 475 020      | 709 475 320       | 26.300         |

| DN<br>(mm) | a<br>(mm) | b<br>(mm) | ID min.<br>(mm) | e<br>(mm) | f<br>(mm) | PN Water<br>(bar) | MOP Gas<br>(bar) |
|------------|-----------|-----------|-----------------|-----------|-----------|-------------------|------------------|
| 80         | 300 - 322 | 210       | 84              | 3xM12     | 100       | 16                | 8                |
| 100        | 359 - 385 | 241       | 90              | 3xM16     | 125       | 16                | 8                |
| 150        | 441 - 478 | 312       | 110             | 4xM16     | 175       | 16                | 8                |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>